



NT-V4 Features

- 1,000 mAh battery backup
- Configurable for 5-second or 10-second live tracking
- Small - 3.684”L x 2.002”W x .775”H - ideal for covert installation
- 3-wire installation for basic tracking (power, ground and ignition)
- Unparalleled dispatch and communications functionality
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Vehicle maintenance module for scheduled fleet service
- External antenna feature for easy installation

The USFT NT-V4

Dimensions	3.684"L x 2.002"W x .775"H
Temperature	-30° C to 75° C (operating) -40° C to 85° C (storage)
Operating Voltage Range	9 - 30 VDC
Power Consumption	Stand by 10mA at 12v Active tracking 70mA at 12v
Cellular Channels	LTE 700/800/850/1700/1800/1900/2600 GSM/GPRS 850/900/1800/1900 CDMA/1xRTT 850/1900 HSPA/UMTS: 850/1900 HSPA Fallback: EDGE/GPRS/GSM quad band EDGE MCS1-MCS9 3GPP Release 6
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 4 additional inputs and 3 outputs at 200mA
Antenna/Modem	External/Internal antenna quad band HSPA+GPS (depending on model) Anti-jamming
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
GPS Receiver	56-channel GPS receiver (with SBAS: WAAS, EGNOS, MSAS, GAGAN)
Diagnostics	Blinking LED diagnostic messages



External antenna device



Power cable



9' external antenna cable

detailed

specifications

 **USFleetTracking**

NT-V4

Manage your fleet on the go.
Download the mobile app, today!

