



# NT-V3 Features

- 1,000 mAh battery backup
- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 4.0"L x 2.0"W x .85"H - ideal for covert installation
- 3 wire installation (power, ground and ignition)
- Unparalleled dispatch and communications functionality
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Vehicle maintenance module for scheduled fleet service
- External antenna feature for easy installation

# The USFT NT-V3

Dimensions	4.0"L x 2.0"W x .85"H
Temperature	-30° C to 75° C (operating)   -40° C to 85° C (storage)
Operating Voltage Range	7 - 32 VDC
Power Consumption	Stand by 20mA at 12v   Active tracking 70mA at 12v
Cellular Channels	HSPA/UMTS: 800/2100 (US)   900/1800 (Europe, Australia, Asia and Middle East) HSPA Fallback: EDGE/GPRS/GSM quad band
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 4 additional inputs and 3 outputs at 200mA
Antenna/Modem	External/Internal antenna   quad band HSPA+GPS (depending on model)   Anti-jamming
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
GPS Receiver	50-channel GPS receiver (with SBAS: WAAS, EGNOS, MSAS, GAGAN)
Diagnostics	Blinking LED diagnostic messages



External antenna device



Internal antenna device



Power cable



9' external antenna cable

	NT-V3	NT-V3ia
Accessories	Power harness/cable	X
	Internal antenna unit	X
	External antenna unit	X
	Monthly subscription	\$29.95

detailed specifications

USFleetTracking

# NT-V3