



AT-V3 Pro Features

- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 4.33"L x 2.125"W x 1.59"H - ideal for fleet tracking
- Rugged, water-resistant housing, solid state circuit - quality throughout
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Hassle free hardware installation - no batteries to replace
- Ignition + 2 inputs and 3 outputs
- 3 wire installation (power, ground and ignition)
- Perfect for Industrial Equipment

The USFT AT-V3 Pro

Dimensions	4.33"L x 2.125"W x 1.59"H
Temperature	Primary power: -30° C to 85° C Battery: -30° C to 70° C
Operating Voltage Range	9 - 32 VDC
Power Consumption	Stand by 37mA at 12 V Active tracking 75mA at 12 V
Cellular Channels	HSPA/UMTS: 800/2100 (US) 900/1800 (Europe, Australia, Asia and Middle East) HSPA Fallback: EDGE/GPRS/GSM quad band
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 2 additional inputs and 3 outputs at 200 mA
Antenna	Internal antenna Quad band HSPA+GPS Anti-jamming 50 channel GPS
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
Backup Battery	3,800 mAh 3 hour charge time 5.2 Ah lithium-ion 6 hour charge time
Diagnostics	Blinking LED diagnostic messages
Shock and Vibration	US Military Standards 202G and 810F, SAEJ1455 RoHS compliant
Enclosure	IP66 Water-resistant



 **USFleetTracking**

AT-V3 Pro