



# AT-V3

## Features

- Great for vehicles, marine, motorcycles and equipment
- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 3.268"L x 2.913"W x .787"H - ideal for covert installation
- Rugged, water-resistant housing, solid state circuit - quality throughout
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Hassle free hardware installation - no batteries to replace
- 3 wire installation (power, ground and ignition)
- Ignition + 1 input and 1 output
- Internal 1,000 mAh backup battery

# The USFT AT-V3

Dimensions	3.268"L x 2.913"W x .787"H
Temperature	-30° C to +75° C (operating)   -40° C to +85° C (storage)
Operating Voltage Range	7 - 32 VDC
Power Consumption	Stand by -18 mA at 12 V   Active tracking -190 mA at 12 V
Cellular Channels	HSPA/UMTS: 800/2100 (US)   900/1800 (Europe, Australia, Asia and Middle East) HSPA Fallback: EDGE/GPRS/GSM quad band
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 1 additional input and 1 output at 150 mA
Antenna/Modem	Internal antenna   Quad band HSPA+GPS   Anti-jamming   50 channel GPS
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
Backup Battery	1,000 mAh   3 hour charge time
Enclosure	IP66   Water-resistant
Shock/Vibration	US Military Standards 202G and 810F, SAEJ1455   RoHS compliant



 **USFleetTracking**

# AT-V3