



AT-X5 Pro

Features >

- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 4.3"L x 3.2"W x 1.6"H - ideal for fleet tracking
- Rugged, water resistant housing, solid state circuit - quality throughout
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Hassle free hardware installation - no batteries to replace
- Ignition + 2 inputs and 3 outputs
- 3 wire installation (power, ground and ignition)

The USFT AT-X5 Pro

Dimensions	4.3"L x 3.2"W x 1.6"H
Operating Temperature	-30° C to 70° C
Operating Voltage Range	9 - 30 VDC
Typical full-power Current	70mA at 12 VDC
GSM Channels	850/1900 (United States) 900/1800 (Europe, Australia, Asia and Middle East)
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 2 additional inputs and 3 outputs
Antenna	Internal dual-mode GSM/GPRS+GPS
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
Backup Battery	700 mAh 3 hour charge time
Diagnostics	Blinking LED diagnostic messages
Shock and Vibration	US Military Standards 202G and 810F, SAEJ1455
Enclosure	IP66 Water-resistant



 **USFleetTracking**

AT-X5 Pro