



OBD-X5

Features >

- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 2.18"L x 1.8"W x 1.08"H - ideal for fleet tracking
- Rugged solid state circuit - quality throughout
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Hassle free hardware installation - no batteries to replace
- OBDII fuel level and instantaneous MPG
- Traffic and live weather Doppler overlay

The USFT OBD-X5

Dimensions	2.18"L x 1.8"W x 1.08"H
Operating Temperature	-30° C to 85° C
Operating Voltage Range	9 - 16 VDC
Typical full-power Current	70mA at 12 VDC
GSM Channels	850/1900 (United States) 900/1800 (Europe, Australia, Asia and Middle East)
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
OBDII Data	Fuel level and instantaneous MPG
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
Applications	Fleet management, theft notification and recovery, teen driver monitoring
Shock and Vibration	In accordance with SAEJ1455
Enclosure	Rugged textured plastic enclosure V fire rated

* features work with certain makes and models



 USFleetTracking

OBD-X5