



# PT-X5

## Features >

- Transmits location every 20 feet if walking, every 10 seconds if driving
- Small - 3.9"L x 2.28"W x .90"H
- No external antenna
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Internal rechargeable Li-ion battery for up to 10 days of 10 second updates
- Internal motion sensor extends battery life
- Small and fast with no wires and no hassle - unlimited possibilities

# The USFT PT-X5

Dimensions	3.9"L x 2.28"W x .90"H
Operating Temperature	-30° C to 75° C
Power Source	3.7V 1340mAh rechargeable Lithium-ion battery, wall charger, USB charger
Typical Full-power Current	150mA during transmission   less than 1mA at rest
GSM Channels	850/1900 (United States) 900/1800 (Europe, Australia, Asia and Middle East)
Update Frequency	Less than 10 mph: once per 20 feet   greater than 10 mph: once per 10 seconds
Antenna	Quad band GSM/GPRS+GPS   integrated into device
Notifications	Multiple alert options (geofences, speed, power, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, speeding report and more...
Applications	Fleet management, theft notification and recovery, teen driver monitoring
Diagnostics	Blinking LED diagnostic messages



 USFleetTracking

# PT-X5