



# VT-X5

## Features >

- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 3.6"L x 2.6"W x 1.0"H - ideal for covert installation
- Rugged, water resistant housing, solid state circuit - quality throughout
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Hassle free hardware installation in just 7 minutes
- 4 inputs and 4 outputs
- 3 wire installation (power, ground and ignition)

# The USFT VT-X5

Dimensions	3.6"L x 2.6"W x 1.0"H
Operating Temperature	-30° C to 75° C
Operating Voltage Range	8 - 16 VDC
Typical Full-power Current	450mA at 12 VDC
GSM Channels	850/1900 (United States) 900/1800 (Europe, Australia, Asia and Middle East)
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 3 additional inputs and 4 outputs
Antenna	Dual-mode GSM/GPRS+GPS   easily concealed under dash
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
Applications	Fleet management, theft notification and recovery, teen driver monitoring
GPS Receiver	16-channel GPS circuit (triangulation from up to 16 concurrent satellites)
Communication Protocol	Blinking LED diagnostic messages



 USFleetTracking

# VT-X5