



AT-V3

Features

- Great for vehicles, marine, motorcycles and equipment
- Configurable for 1-second, 5-second or 10-second live tracking
- Small - 3.0"L x 2.5"W x .75"H - ideal for covert installation
- Rugged, water-resistant housing, solid state circuit - quality throughout
- Multiple alert notifications by email or text message (geofences, speed, etc.)
- 100% web-based | no software to install | accessible from anywhere
- Hassle free hardware installation - no batteries to replace
- 3 wire installation (power, ground and ignition)
- Ignition + 1 input and 1 output
- Internal 200 mAh backup battery

The USFT AT-V3

Dimensions	3.0"L x 2.5"W x .75"H
Temperature	-30° C to +75° C (operating) -40° C to +85° C (storage)
Operating Voltage Range	9 - 32 VDC
Power Consumption	Stand by - 10mA at 12/24 VDC Active tracking - 60mA at 12 VDC
Cellular Channels	HSPA/UMTS: 850/1900 (US) 900/1800 (Europe, Australia, Asia and Middle East) HSPA Fallback: EDGE/GPRS/GSM quad band
Update Frequency	1-second, 5-second or 10-second position updates (truly live tracking)
Input/Output	1 ignition input, 1 additional input and 1 output at 150 mA
Antenna/Modem	Internal antenna Quad band HSPA+GPS Anti-jamming 56 channel GPS
Notifications	Multiple alert options (geofences, speed, ignition, etc.) via text message or email
Historical Playback	90 days of historical playback stored at server
Reporting	Individual vehicle report, start/stop report, excessive idling report and more...
Backup Battery	200 mAh 3 hour charge time
Enclosure	IP66 Water-resistant
Shock/Vibration	US Military Standards 202G and 810F, SAEJ1455 RoHS compliant



Manage your fleet on the go.
Download the mobile app, today!



 **USFleetTracking**

AT-V3